

Elastic properties of natural single nanofibres

A. Carnicero López; E. Ruiz-Hitzky; F.M. Fernandes; L.F. Vázquez Burgos; M. Castro Ponce

Abstract-

Natural nanomaterials are becoming increasingly relevant in the context of mechanical reinforcement of a multiplicity of matrices. The elastic properties of single nanomaterials are, however, mostly unknown. By combining two different - and complementary - AFM strategies we determined the elastic properties of single clay sepiolite nanofibres to be 8.2 ± 2.5 GPa in bending mode. We took advantage of the silanol-rich sepiolite surface to covalently graft it onto a micropatterned silicon substrate to achieve an experimental setup with clearly defined boundary conditions. The determination of the elastic properties of single nanofibres was completed by the determination of the elastic moduli at other length scales and their behaviour from the macro- to the nano-scale is discussed.

Index Terms-

Due to copyright restriction we cannot distribute this content on the web. However, clicking on the next link, authors will be able to distribute to you the full version of the paper:

[Request full paper to the authors](#)

If your institution has an electronic subscription to RSC Advances, you can download the paper from the journal website:

[Access to the Journal website](#)

Citation:

Carnicero, A.; Castro, M.; Fernandes, F.M.; Ruiz-Hitzky, E.; Vázquez, L. "Elastic properties of natural single nanofibres", *RSC Advances*, vol.2014, no.4, pp.11225-11231, December, 2014.